

# PDA 6200S series

## Stereo Power Amplifier



### Feature

PDA 6212S/ 6224S is STEREO CLASS-D PA Amplifier with (2x120Watt)/ (2x240Watt) @ 4Ω and (1x240W) / (1x480Watt) @ Hi-Z.

- Compact 1 HU high / Half size and Full size format.
- 4Ω or 70V/100V system.
- Hi-Z output with 70Hz HPF filter and is isolated with a transformer.
- PA Mute function (TEL>AUX).
- Limiter, output short, overheat protection.
- Passive cooling.
- Tabletop or System Rack-mount.

Performance	PDA 6212S	PDA 6224S
Max Output Power @ 4Ω 1kHz ≤ 1% THD	2x120W	2x240W
Input Sensitivity & Impedance	TEL: 100V/1V @600Ω, Balanced AUX: 1V @600Ω, Stereo	
Frequency Response	4Ω Output: 20~20kHz, +1/-3 dB 70/100V Output: 80Hz~18kHz, +1/-3dB	
S/N Ratio	TEL >70dB AUX >75dB	
Nominal AC Line Voltage	100~240V, 50/60Hz	
Operation Temperature / Humidity	-10°C ~ +45°C @ 95% R.H. (Non-Condensing)	
Storage Temperature	-20°C ~ +70°C	
Dimensions (W x D x H:mm)	215 x 315 x 44	430 x 315 x 44
Weight	3.9kg	4.3kg



- LED Ring to indicate output level (VU meter).
- Power ON/OFF button.

### Front Panel

### Rear Panel

- TEL/EMG Input.
- TEL/EMG input level Gain control.
- Dipswitch:
  - TEL/EMG Enable/Disable.
  - Hi-Z/HPF.
- AUX level control.
- RCA Stereo Input.

- Remote Panel RJ45 Connector.
- 4Ω (STEREO) /70V/100V (MONO) Output Phoenix connector.
- AC Input.

